

450/750V 及以下 BV-105 电线敷设在明敷导管内的载流量(A)

线芯截面	导线根数	环境温度(°C)			
		50	55	60	65
1.5	2	19	18	17	16
1.5	3	17	16	15	14
1.5	4	16	15	14	13
2.5	2	27	25	24	23
2.5	3	25	23	22	21
2.5	4	23	21	20	19
4.0	2	39	37	35	33
4.0	3	34	32	30	28
4.0	4	31	29	28	26
6.0	2	51	48	46	43
6.0	3	44	41	39	37
6.0	4	40	38	36	34
10.0	2	76	72	68	64
10.0	3	67	63	60	57
10.0	4	59	56	53	50
16.0	2	95	90	85	81
16.0	3	85	81	76	72
16.0	4	75	71	67	63
25.0	2	127	121	114	108
25.0	3	113	107	102	96
25.0	4	101	96	91	86
35.0	2	160	152	144	136
35.0	3	138	131	124	117
35.0	4	126	120	113	107
50.0	2	202	192	182	172
50.0	3	179	170	161	152
50.0	4	159	151	143	135
70.0	2	240	228	217	204
70.0	3	213	203	192	181
70.0	4	193	184	174	164
95.0	2	292	278	264	249
95.0	3	262	249	236	223
95.0	4	233	222	210	198
120.0	2	347	331	314	296
120.0	3	311	296	281	265
120.0	4	275	261	248	234
150.0	2	399	380	360	340

150.0	3	362	345	327	308
150.0	4	320	305	289	272